

90+ | 素色肌肤砖



Traver Cave
罗马假日



90+ | 素色肌肤砖

广东省佛山市禅城区塑宝西路60号
欧洲工业园二座三层自编之C区
C Area, Level 3, Building 2, European Industrial Park,
No. 60, West Langbao Road, Foshan City,
Guangdong Province, P.R.China

90+



90+ 罗马假日系列，条纹清晰，模具还原天然的孔洞，立体感十足。高达P4的防滑值，让脚下更安全。

采用环保材料，共三色可供选择。一石多面，纹理多样，带来丰富的视觉感受。不仅适合在家中铺贴，也可以应用于各种商业场所和公共场所。

Travercave series has clear stripes and natural holes restored by the mold, creates a full sense of three-dimensional. It can achieve P4 anti-slip rate, making the tile surface safer.

It is made of environment-friendly materials, with three colors available. One stone has different patterns and various textures, bringing rich visual experience. It is not only suitable for paving at home, but also can be used in various commercial places and public places.

米白
OFF-WHITE

60TC20R/URD
600x600mm

银灰
SILVER GREY

60TC21R/URD
600x600mm

米黄
IVORY

60TC22R/URD
600x600mm



明亮的米白纯洁干净，形态各异的孔洞肌理，搭配层层叠加的纹理，将大自然的景观带入空间。

The bright off white is pure and clean, with different hole textures and overlapping textures, bringing the natural landscape into the space.

米白
OFF-WHITE

60TC20R/URD
600x600mm



FLOOR:60TC20R





银灰色调有着神秘的气质，运用在空间中尽显尊贵和华丽。

The silver grey color has a mysterious temperament, which shows its dignity in the space. You can feel the beauty of nature without leaving home.

银灰
SILVER GREY

60TC21R/URD
600x600mm



FLOOR:60TC21R





米黄，给人带来温暖的感受，每一个细节都做到极致，完美再现洞石的纹理，带来视觉和触觉的双重享受。

Ivory color brings a warm feeling to people. Every detail is perfect. The texture of the cave stone is perfectly reproduced, bringing both visual and tactile enjoyment.

米黄
IVORY

60TC22R/URD
600x600mm



FLOOR:60TC22R



INSTALLATION GUIDANCE 安裝指南



TEXTURE RATING 纹理评级	MIN.LAYING GAP 3mm 最小铺设间隙3mm	RECTIFIED 精准的尺寸	STRUCTURE 模具	WALL TILES 墙砖	FLOOR TILES 地砖	COLOURS 颜色	SIZES 尺寸	SURFACES 表面效果
--	---	--	---	--	---	---	---	--



Dimensions & Surface Quality			
Length and Width 长度和宽度	±0.6% max.	-0.03-0.03%	-0.03-0.03%
Thickness 厚度	±5% max.	9.0-9.5mm	11.0-11.5mm
Orthogonality 直角度	±0.5% max.	-0.06-0.07%	-0.06-0.07%
Straightness of sides 边直度	±0.5% max.	-0.06-0.07%	-0.02-0.03%
Surfaces flatness 表面平整度	±0.5% max.	-0.05-0.07%	-0.09-0.11%
Physical Properties			
Water absorption 吸水率	≤0.5%	≤0.5%	≤0.5%
Breaking strength 断裂强度	≥1300N	2265N	4031N
Bending resistance 抗弯曲性	≥35N/mm ²	38N/mm ²	40N/mm ²
Resistance to deep abrasion 耐磨程度	≤175mm ³	Class 4	Class 4
Temperature shock resistance 耐高低温系数	No visible crack 没有明显裂纹	No visible crack 没有明显裂纹	Durable 耐温性好
Resistance to frost 防冻性能	No visible crack 没有明显裂纹	No visible crack 没有明显裂纹	No visible crack 没有明显裂纹
Non-slip 防滑系数	R9-R11	R11	R11
Colour resistance to light 颜色耐光性	no colour changes 不褪色	no colour changes 不褪色	no colour changes 不褪色
Chemical Properties			
Chemical resistance 耐化学性	no visible changes when subjected to chemicals 遇化学物质不受影响	Durable 耐化学性能好	Durable 耐化学性能好
Resistance to staining 抗染色	≥3	Class 5 5级	Class 5 5级

600x600mm	✓		4	1.44	31.5